

## 5 MP AHD IR Water-proof Dome Camera



Sensor 1500TVL Min. illumination BLC WDR





Day&Night Auto WB Sync AGC Water-proof

## Features

- 5MP image, high resolution, true color
- AHD / TVI lossless video output
- Up to 1500 TVL resolution
- CMOS progressive scan, perfectly capture the moving object
- WDR
- Support OSD menu
- High speed, long distance, real time transmission
- Auto color to B / W at low illumination
- Support ICR switch, true day / night
- Support noise reduction function
- 10 ~ 20m IR night view distance
- IP66 ingress protection
- Support COC

## Dimensions



## Specifications

Model	TVI5-D7554-28 / TVI5-D7554-36
<b>Specifications</b>	
<b>Camera</b>	
Image Sensor	1 / 2.5" CMOS
Resolution	5MP
Image Size	2592 x 1944
Video Output	AHD / TVI
Image System	PAL / NTSC
Electronic Shutter	Auto; 1 / 25s ~ 1 / 100000s ( PAL ); 1 / 30s ~ 1 / 100000s ( NTSC )
IR Distance	10 ~ 20 m
Frame Rate	20fps
Min. Illumination	Color : 0.001 lux@F1.2, AGC ON; B/W : 0 lux with IR
Lens	3.6 mm ( 2.8 mm optional )
Lens Mount	M12
S / N Ratio	≥52dB ( AGC OFF )
Ingress Protection	IP66
<b>Functions</b>	
Function Control	OSD ( COC Control )
Day & Night	ICR
Digital WDR	
Digital NR	Yes ( 2D DNR )
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Edge Brightness Compensation	Yes
Defogging	Yes
HLC	
Sharpness	Yes
Mirror Image	Yes
Smart IR	Yes
Image Setting	Yes
Defect Correction	Auto / Manual
Language	13 different languages
Angle Adjustment	Any angle
<b>Others</b>	
Power Supply	DC12V ( ± 10% )
Power Consumption	IR OFF : < 1W; IR ON : < 3W
Working Environment	- 20 °C ~ 50 °C, 10 % ~ 90 % ( relative humidity )
Dimensions ( mm )	Φ 87 x 108